

LSZC - BUOCHS

LSZC AD 2.1 AERODROME LOCATION INDICATOR AND NAME

LSZC - BUOCHS

LSZC AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at Aerodrome	46 58 28 N 008 23 49 E RWY midpoint
2	Direction and distance from the CITY	2 km W Buochs
3	Elevation/Reference temperature	1475 ft AMSL - 24.7°C
4	MAG VAR/Annual change	2° E (2016.5) / 0° 9.7' eastwards
5	AD Administration, address, telephone, telefax, telex, AFS	Post: Airport-Buochs AG Fadenbrücke 20 CH-6374 Buochs Phone: +41 (0) 41 622 06 11 Fax: +41 (0) 41 622 06 10 TWR: +41 (0) 41 624 59 01 AFS: LSZCZTX Email: info@airportbuochs.ch URL: http://www.airportbuochs.ch/
6	Types of traffic permitted (IFR/VFR)	IFR/VFR
7	Remarks	Geodetic undulation reference for ARP: 158.8 ft

LSZC AD 2.3 OPERATIONAL HOURS

1	AD Administration	MON - FRI: 0700 - 1105 (0600 - 1005) / 1215 (1115) - SS MAX 1900 (1800) SAT: 0700 - 1100 (0600 - 1000) / 1300 (1200) - SS MAX 1900 (1800) SUN/HOL: 0900 - 1100 (0800 - 1000) / 1300 (1200) - SS MAX 1700 (1600) HOL: REF AIP GEN 2.1.6. , Local HOL REF LSZC AD 2.2.2
2	Customs and immigration	REF LSZC AD 2.20
3	Health and sanitation	NIL
4	AIS Briefing Office	AD OPR HR
5	ATS Reporting Office (ARO)	NIL
6	MET Briefing Office	NIL; REF LSZC AD 2.11
7	ATS	0630 - 1105 (0530 - 1005) and 1215 - 1605 (1115 - 1505) MON - FRI. Other times O/R. MNM 24 HR prior DEP, MNM 3 days ARR due skyguide and CUST. REF LSZC AD 2.20
8	Fuelling	O/R
9	Handling	Limited service O/R during AD OPR HR
10	Security	NIL
11	De-icing	NIL
12	Remarks	AD: PPR

LSZC AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo handling facilities:	NIL
2	Fuel/oil types	Jet A1
3	Fuelling facilities/capacity	By fuel truck
4	De-icing facilities	NIL
5	Hangar space available for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	By Pilatus Ltd. maint O/R, limited to Pilatus ACFT only
7	Remarks	NIL

LSZC AD 2.5 PASSENGER FACILITIES

1	Hotels	Close to AD and surrounding cities
2	Restaurants	Close to AD and surrounding cities
3	Transportation	Taxis
4	Medical facilities	Hospital in the city (Stans)
5	Bank and Post Office	In the city
6	Tourist Office	NIL
7	Remarks	NIL

LSZC AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	O/R Category 1 - 5, 24 HR before ETD / ETA
2	Rescue equipment	2 fire trucks
3	Capability for removal of disabled aircraft	Up to 5.7 tonnes immediately, others O/R
4	Remarks	NIL

LSZC AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Type(s) of clearing equipment	Snow removal available O/R
2	Clearance priorities	RWY, TWY, Apron
3	Remarks	All seasons

LSZC AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	ASPH: PCN 45/F/BX/U
2	Taxiway width, surface and strength	Width: TWY A: 12.0 m TWY B, C: 12.0 m TWY D: min 10.1 m, BTN TWY B - Pilatus factory 9.4 m, TWY E: 12.0 m; TWY F: 9.8 m. Surface: ASPH: PCN 45/F/BX/U
3	ACL location and elevation	NIL
4	VOR/INS checkpoints	NIL
5	Remarks	NIL

LSZC AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM, MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Guidance sign boards, TWY CL
2	RWY/TWY markings and LGT	RWY, TWY and holding position markings
3	Stop bars	NIL
4	Remarks	NIL

LSZC AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas				In circling area and at aerodrome		3
1				2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Co-ordinates	Obstacle type Elevation Markings/LGT	Co-ordinates	RMK	
a	b	c	a	b	c	
		ft		ft		
AOC 24 (1)	Tree/Trees 1517	46 58 14 N 008 22 57 E	Crane/Cranes marked/LGTD 1523	46 58 43 N 008 24 52 E	B0365/14	
AOC 24 (2)	Tree/Trees 1521	46 58 07 N 008 22 55 E	Silo LGTD 1468	46 58 44 N 008 24 50 E	B1468/19	
AOC 24 (3)	Tree/Trees 1528	46 58 05 N 008 22 52 E	Crane/Cranes marked/LGTD 1644	46 59 02 N 008 24 23 E	B0941/19	
AOC 24 (4)	Building 1649	46 57 25 N 008 21 23 E	Crane/Cranes marked/LGTD 1559	46 58 12 N 008 24 07 E	B0146/20	
AOC 24 (5)	Power line 1698	46 57 23 N 008 21 19 E	Crane/Cranes marked/LGTD 1600	46 57 36 N 008 21 58 E	B0181/20	
AOC 24 (6)	Tree/Trees 1706	46 57 22 N 008 21 11 E	Crane/Cranes marked/LGTD 1565	46 58 23 N 008 24 47 E	B0042/20	
AOC 24 (7)	Pole 1929	46 57 18 N 008 20 57 E	Crane/Cranes marked/LGTD 1647	46 57 29 N 008 21 21 E	B0284/20	
AOC 24 (8)	Tree/Trees 2163	46 57 11 N 008 20 50 E	Crane/Cranes marked/LGTD 1520	46 58 44 N 008 24 56 E	B0452/20	
AOC 24 (9)	Tree/Trees 2278	46 56 57 N 008 20 17 E	Crane/Cranes marked/LGTD 1598	46 57 33 N 008 21 49 E	B0682/20	
AOC 24 (10)	Tree/Trees 2316	46 57 19 N 008 19 18 E				
AOC 24 (11)	Pole 2838	46 57 17 N 008 19 10 E				
AOC 24 (12)	Tree/Trees 2860	46 57 17 N 008 19 10 E				
AOC 24 (13)	Pole 2868	46 57 17 N 008 19 09 E				
AOC 24 (14)	Antenna 2934	46 57 17 N 008 19 09 E				

LSZC AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	MeteoSwiss
2	Hours of service	H24
3	Office responsible for TAF preparation Periods of validity	MeteoSwiss, Zurich 9 hours
4	Type of landing forecast	Trend; issuance: HH+20, HH+50
5	Briefing/consultation provided	Self Briefing Service (www.skybriefing.com)
6	Flight documentation Language(s) used	-- En
7	Charts and other information available for briefing or consultation	NIL
8	Supplementary equipment available for providing information	NIL
9	ATS units provided with information	ATS Buochs
10	Additional information (limitation of service, etc.)	Tel weather briefing: 0900 162 737 (GE), accessible within Switzerland

LSZC AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE & MAG BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY REF AD 1.1.6.2.3	THR COORD	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
06	064/062	2000 X 40	PCN 45/F/B/X/U ASPH	46 58 14.63 N 008 23 08.89 E	1475 ft	-0.6%
24	244/242			46 58 40.91 N 008 24 28.97 E	1435 ft	+0.6%

Designations RWY NR	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	OFZ	Remarks REF: AD 1.1.
1	8	9	10	11	12
06	NIL	NIL	2120 X 150	NIL	Non-instrument RWY FCT: 0.98 / 0.97 no FCT measuring EQPT AVBL
24					

LSZC AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
06	2000 m	2000 m	2000 m	1940 m	NIL
24	2000 m	2000 m	2000 m	1940 m	NIL

LSZC AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type LEN INTST	THR LGT colour WBAR	VASIS (MEHT) PAPI	TDZ Length	RWY Centre Line LGT Length, spacing, colour, INTST	RWY edge LGT LEN, spacing, colour, INTST	RWY End LGT colour WBAR	SWY LGT LEN (m) colour	Remarks
1	2	3	4	5	6	7	8	9	10
06	ALS LIH	RTHL G LIH WBAR	MIL PAPI: 4°	NIL	NIL	REDL 60m W LIH	RENL R WBAR	NIL	RWY and APCH LGT not ICAO Standard
24									

LSZC AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	NIL
2	LDI location and LGT Anemometer location and LGT	NIL
3	TWY edge and centre line lighting	NIL
4	Secondary power supply/switch-over time	NIL
5	Remarks	NIL

LSZC AD 2.16 HELICOPTER LANDING AREA

1	Coordinates TLOF or THR of FATO	NIL
2	TLOF and/or FATO elevation M/FT	NIL
3	TLOF and FATO area dimensions, surface, strength, marking	NIL
4	True and MAG BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	TLOF and Stand PSN as indicated by the marshaller

LSZC AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	Buochs CTR O/R 47 03 00 N 008 28 20 E - 46 58 56 N 008 30 22 E - 46 57 46 N 008 30 42 E - 46 55 47 N 008 20 27 E - 47 00 37 N 008 18 33 E - 47 01 50 N 008 20 18 E - 47 03 00 N 008 28 20 E
2	Vertical limits	FL 130
3	Airspace classification	D
4	ATS unit call sign Language(s)	En
5	Transition altitude	7000 ft AMSL
6	Remarks	HX

LSZC AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of Operation	Remarks
1	2	3	4	5
TWR	Buochs Tower	119.625	HX	HX
AD - Information	Buochs	134.130	H24	HX Status Information Buochs and Alpnach

LSZC AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type Category (Variation)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
NIL	NIL	NIL	NIL	NIL	NIL	NIL

LSZC AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Customs:

Customs will be informed by AD Operator after receipt of FLT announcement on <http://www.airportbuochs.ch>.

Lead time:

Flights to Schengen area: 2 HR before ETD, 3 HR before ETA

Flights to third countries (Non-Schengen): 24 HR before ETD and ETA

- no commercial goods

- no tax-free fuel

2. Local flying restrictions:

2.1 The Airport is CLSD on the following days:

Good FRI, Federal Prayday (3rd SUN in SEP), Christmas Day (25 DEC)

2.2 Local HOL:

Joseph's Day (19 MAR), Corpus Christi, Assumption Day, All Saints' Day (01 NOV), Immaculate Conception (08 DEC)

2.3 Other than normal OPS:

AD circuits, aerobatics, PJE and HEL OPS are restricted in accordance with the AD operating regulations. Appropriate information will be given by the AD authority.

2.4 TKOF outside TWR OPR HR:

Outside TWR OPR HR, TKOF and LDG must be performed from the beginning of RWY.

INT TKOF are prohibited.

2.5 Flight operations outside TWR OPR HR:

- ARR and DEP ACFT have to apply on radio the procedure for blind transmissions.

- FREQ: 119.625 MHz

For all FLTs outside TWR OPR HR, the AP manager must be mobilised for non home-based pilots.

If ATC has to be provided outside TWR OPR HR, a charge for each operation will be levied.

No IFR APCH outside TWR OPS.

REF <http://www.airportbuochs.ch> (Fees: Tariffs and Charges).

3. ACFT guidance on apron

ACFT movement (TAX) during TWR OPR HR and with marshaller only.

4. Departure

At start-up, ACFT PSN must be reported.

5. RWY Arresting gear and Net barrier

RWY arresting gear (RAG) and Net barrier removed.

6. High-visibility jacket

It is mandatory for all personnel remaining in the movement areas (ACFT, PRKG, TWY, RWY) to wear safety jackets. A yellow high-visibility safety jacket which complies with the EN471 standard must be worn.

7. Pilatus Aircraft Ltd. operations**ONLY FOR PILOTS OPERATING FOR PILATUS AIRCRAFT LTD****7.1 Traffic light to Pilatus Aircraft Ltd:**

A traffic light regulates traffic between the public road and TWY D to Pilatus Aircraft Ltd. The system shall be ACT by the pilot himself. TWR FREQ may therefore be left for short moments. Aeroplanes on then Pilatus area shall request TAX clearance from the TWR before entering TWY D.

User instruction:

- Activation with three short radio SGL on 121.905 MHz, before crossing the inductive loop on TWY D. A sharp whistle follows as confirmation. Only then CONT slowly towards the crossing and cross over when the light turns green.
- The traffic light remains green for 2 MIN.
- If the traffic light cannot be ACT, contact TWR (OPR HR see AD 2.18). Otherwise give way to road traffic and cross the road at own risk.
- TWR cannot activate the traffic light once the aeroplane has crossed the inductive loop.

7.2 Traffic light to H10:

A traffic light regulates traffic between the public roads and TWY C to H10. The system shall be ACT by the pilot himself. TWR FREQ may therefore be left for short moments. Aeroplanes on area in front of H10 shall request TAX clearance from the TWR before entering TWY C.

User instruction:

- Activation with three short radio SGL on 121.705 MHz in an interval of half a second. A sharp whistle follows as confirmation. Only then, CONT slowly towards the crossing and cross over when the light turns green.
- The traffic light remains green for 2 MIN.
- If the traffic light cannot be ACT, give way to road traffic and cross the road at own risk or request a "follow-me" car from TWR.

7.3 Barrier remote control RWY 06/24 (middle of the RWY) outside TWR OPR HR:

- Instruction mandatory
- To activate the system, TRANS four short radio SGL on FREQ 119.625 MHz (at intervals of half a second).
- The barriers will be lowered within 30 sec and will remain CLSD for 4 MIN.
- After TKOF or LDG, the system shall be deactivated by transmitting six short radio SGL.
- The system will confirm by an automatic voice message the closure of the barriers as soon as they are lowered and the RWY lighting is on.
- No TKOF and LDG with OPN barrier. Without acoustic confirmation no TKOF or LDG permitted.
- Barriers must also be CLSD for backtracking.

LSZC AD 2.21 NOISE ABATEMENT PROCEDURES**1. Auxiliary Power Unit (APU)**

APU shall be started no earlier than 30 MIN before off-block time and kept in operation no longer than 30 MIN after the on-block time.

LSZC AD 2.22 FLIGHT PROCEDURES

1. Special regulations for IFR approach and departure

1.1 IFR procedure

1.1.1 SID Descriptions

Procedure limited to pilots operating for Pilatus Aircraft Ltd.

1.1.1.1 SID RWY 24

DESIGNATOR	RWY 24 - NON RNAV - (see chart LSZC AD 2.24.7-1)			
	ROUTE			
	Lateral	Vertical	Contact	Remark
WILLISAU 2A (WIL 2A) PDG 13.7% to 7300ft MNM Climb gradient 13.7% to 8000ft to remain inside controlled Airspace.	Climb on CRS244. When crossing R158 (ZC601) turn right (MAX IAS 230kt during turn) and intercept R158 WIL inbound WIL. Proceed to WIL VOR/DME.	INITIAL CLIMB CLEARANCE FL100	NIL	Day only

1.1.2 STAR Descriptions

SPEED LIMITATION: General: Below FL 100 MAX IAS 250kt.
--

DESIGNATOR	STAR TO RONIX - RNAV1 (see chart LSZC AD 2.24.9-1)		
	ROUTE		
	Lateral	Vertical	Remark
ASGED 1F	From ASGED proceed to RONIX.	Refer to chart	MAX IAS 200 kt at ASGED MAX IAS 180 kt at RONIX
WILLISAU 2F (WIL 2F)	From WIL proceed to RONIX	Refer to chart	MAX IAS 180 kt at RONIX

Procedure Description of RNAV STAR ASGED 1F (see chart LSZC AD 2.24.9-1)						
Path terminator	Waypoint	Flyover	Altitude (ft)	Speed limit (kt)	Track	Distance (NM)
-	ASGED	N	-	200	-	-
TF	RONIX	N	+6000	180	261° (263.0°T)	4.7

Procedure Description of RNAV STAR WIL 2F (see chart LSZC AD 2.24.9-1)						
Path terminator	Waypoint	Flyover	Altitude (ft)	Speed limit (kt)	Track	Distance (NM)
-	WIL	N	-	-	-	-
TF	RONIX	N	+6000	180	081° (082.5°T)	22.7

1.1.3 Approach procedure**1.1.3.1 Special regulation for IFR approach RNP A**

Procedure limited to pilots operating for Pilatus Aircraft Ltd.

The APCH shall be used during HR of daylight only.
CTR 2 Emmen needs to be ACT for APCHs below 3500 ft AMSL.

1.1.3.2 RAIM

No NOTAM RAIM service will be provided. It is the operator's responsibility to check RAIM availability. Due to the high terrain, a mask angle of 12.5 DEG should be chosen. EUROCONTROL provides the AUGUR tool for checking RAIM. It is AVBL from the following link: <http://augur.eurocontrol.int>

1.1.3.3 Procedure description

Procedure Description of RNP A (see chart LSZC AD 2.24.10-1)						
Path terminator	Waypoint	Flyover	Altitude (ft)	Speed limit (kt)	Track	Distance (NM)
-	RONIX	N	+6000	180	-	-
TF	ZC700	N	-	150	129° (130.7°T)	3.6
TF	ZC701	N	-	-	181° (182.9°T)	2.0
TF	KUSIX	N	+4500	-	216° (217.9°T)	2.7
TF	ZC760	Y	-	-	216° (217.8°T)	5.6
DF	ZC752	N	-	150	-	-
TF	ZC753	N	-	-	038° (039.9°T)	5.6
TF	RONIX	N	+6000	-	082° (083.5°T)	9.3

1.2 VFR procedure

Refer to VFR Manual, LSZC AD INFO.

1.3 Supplementary provisions regarding VFR-flights

Refer to VFR Manual, LSZC AD INFO.

2. Minima for IFR departures (TKOF minima)

RWY	ACFT CAT	RVR (m) / Ceiling (ft AGL)			RMK
		No LGT AVBL	REDL or RCLL AVBL	REDL and RCLL AVBL	
24	A	1400/---	1400/---	---	NIL
	B	1400/---	1400/---	---	
	C	1400/---	1400/---	---	
	D	1400/---	1400/---	---	

LSZC AD 2.23 ADDITIONAL INFORMATION

1. List of significant points (Terminal)

NAV point	COORD WGS84		Purpose
	LAT	LONG	
1	2		3
KUSIX	N 47 07 06.8	E 008 28 47.0	RNP APCH LSZC
ZC601	N 46 52 22.6	E 008 04 04.6	SID LSZC
ZC700	N 47 11 14.6	E 008 31 23.3	RNP APCH LSZC, GNSS LFN on trial
ZC701	N 47 09 16.6	E 008 31 14.7	RNP APCH LSZC
ZC752	N 47 08 13.3	E 008 08 36.2	RNP APCH LSZC
ZC753	N 47 12 32.6	E 008 13 54.5	RNP APCH LSZC
ZC760	N 47 02 41.4	E 008 23 45.7	RNP APCH LSZC

2. Bird concentrations in the vicinity of the airport

Tracer shots will be fired OCNL.

LSZC AD 2.24 CHARTS RELATED TO AN AERODROME

Name	Page
Aerodrome Chart	LSZC AD 2.24.1-1
Aerodrome Obstacle Chart - Type A - RWY 24	LSZC AD 2.24.4.1
SID RWY 24 - NON RNAV	LSZC AD 2.24.7.1
STAR to RONIX - RNAV 1	LSZC AD 2.24.9-1
IAC RNP A CAT A/B	LSZC AD 2.24.10-1
IAC VIS APCH	LSZC AD 2.24.10-3